


# Madame Blanche\_P2



Pendant Luminaires | 220-240 V | topLED 32 W 700 mA | DALI | CRI 90  
8178



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	32 W
Luminous flux (source)	3929 lm
Frequency	50 - 60 Hz
CCT / Tonaltà	3000 K
Colour rendering index	90 Ra
AC / DC	AC
Safety class	1
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	DALI
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	4 m
Electric socket	Type F+E
Resin potting	No
Net weight	4.055 Kg

Finishing casing	
Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating

Finishing diffuser	
Material	PMMA
Colour	white
Processing	Satin finishing

# Madame Blanche\_P2



Pendant Luminaires | 220-240 V | topLED 32 W 700 mA | DALI | CRI 90  
**8178**

Double emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 156 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3929 lm, with a 122.8 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pmma with a satin finishing treatment. The ingress protection degree is IP20; the total weight is of 4.055 kg. The power supply driver is included in the delivery.

The total absorbed power is 32 W. The power supply cable is included and features.

The device features protection class I and can be ceiling-mounted.

## Illuminotechnical Features

Luminous flux (source)	3929 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20