

# **PRODUCT DATASHEET** HALOSTAR PRO 35 W 12 V GY6.35

# HALOSTAR PRO | Low-voltage halogen lamps with pin base



#### AREAS OF APPLICATION

- General illumination
- Kitchen lighting
- Lighting for reading
- Entrance lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Outdoor applications only in suitable luminaires

#### **PRODUCT BENEFITS**

- Brilliant accent lighting
- Significantly lower  $CO_2$  emissions compared to standard version
- High luminous efficacy compared with standard lamps
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

#### **PRODUCT FEATURES**

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index R<sub>a</sub>: 100
- IRC technology

# **TECHNICAL DATA**

## Electrical data

Nominal wattage	35.00 W
Nominal voltage	12 V
Rated wattage	35.00 W
Power factor λ	1.00
Claimed equiv. conventional lamp power	50 W


#### Photometrical data

Nominal luminous flux	860 lm
Rated color temperature	2900 К
Light color (designation)	Warm White
Rated luminous flux	860 lm
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.80

# Light technical data

Starting time	0.0 s
Warm-up time (60 %)	0.00 s

# Dimensions & weight



Diameter	12.0 mm
Overall length	44.0 mm
Light center length (LCL)	30.0 mm
Length	44.0 mm
Outer bulb	E12
Maximum diameter	12.0 mm

## Lifespan

#### PRODUCT DATASHEET

Nominal lamp life time	4000 h
Rated lamp life time	4000 h
Number of switching cycles	100000

## Additional product data

Base (standard designation)	GY6.35
Mercury content	0.0 mg
Mercury-free	Yes

## Capabilities

Burning position	Any
Dimmable	Yes


#### Certificates & standards

Energy efficiency class	В
Energy consumption	38 kWh/1000h

## Country specific categorizations

ILCOS	HSGS/C/AXUBIB-35-12-GY6.35-12/30
-------	----------------------------------

# Light Distribution



# Spectral power distribution

# LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300615905	HALOSTAR PRO 35 W 12 V GY6.35	Shipping carton box 40	125 mm x 127 mm x 121 mm	1.92 dm³	197.40 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.