

PRODUCT DATASHEET

DALI magic

DALI magic | USB to DALI programming interface



AREAS OF APPLICATION

- Configuration of DALI ECG functions
- Monitoring of DALI installations

DALI WIZARD SOFTWARE FEATURES (INCLUDED)

- Intuitive configuration of up to 64 DALI electronic control gears
- Offline / Online configuration of DALI installations
- "DALI-Spy"-functionality for recording DALI line data flow

DALI WIZARD SOFTWARE FEATURES (INCLUDED)

- Intuitive configuration of up to 64 DALI electronic control gears
- Offline / Online configuration of DALI installations
- "DALI-Spy"-functionality for recording DALI line data flow

TUNER4TRONIC SOFTWARE FEATURES

- Programming of OSRAM ECG
- Suitable for the shop floor environments
- Performs fast manual and automatic programming
- Easily enables the use of the pre-parameterization service

TUNER4TRONIC SOFTWARE FEATURES

- Programming of OSRAM ECG
- Suitable for the shop floor environments
- Performs fast manual and automatic programming
- Easily enables the use of the pre-parameterization service

PRODUCT FAMILY FEATURES


- USB DALI converter for Tuner4TRONIC and DALI wizard software for Windows PC
- Pushbutton to test DALI dimming without need of connection to computer
- Powered by USB or by included universal power supply
- Integrated automatic DALI supply of up to 64 devices (up to 4 if powered by USB)

TECHNICAL DATA

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
System wattage [AGGR]	7.00 W

Dimensions & weight



Length	120.0 mm
Width	76.0 mm
Height	28.0 mm
Product weight	370.00 g

Colors & materials

Product color	White
----------------------	-------

Temperatures & operating conditions

Ambient temperature range	+15...+50 °C
----------------------------------	--------------

Capabilities

Dimmable	Yes
-----------------	-----





Certificates & standards

Type of protection	IP20
---------------------------	------

EQUIPMENT / ACCESSORIES

- Universal power supply (100...240 V_{AC}, 5.9 V_{DC}, 1.15 A, EU plug)
- USB cable (male A to male B), 180 cm
- Bipolar plug for DALI connection

DOWNLOAD DATA

File	
	Brochures 336599_LMS 3 DIM Flyer (GB)
	Declarations of conformity 334886_Declaration of conformity – DALI magic
	Installation/Operation notice 334217_Technical instruction
	CAD data 3-dim 328821_DALI MAGIC

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899039551	Shipping carton box 1	148 mm x 98 mm x 135 mm	376.00 g	1.96 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

Compatible software available at

- ▶ www.ledvance.com/software

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.