




220-240 V | topLED 32 W 700 mA | CRI 90
8516



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	32 W
Luminous flux (source)	4145 lm
Frequency	60 - 50 Hz
CCT / Tonalità	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	Phase cut
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	Wood
Colour	white
Processing	melamine

Finishing diffuser	
Material	PE
Colour	neutral

Finishing mounting frame	
Material	Iron
Colour	embossed white RAL 9003
Processing	Coating



220-240 V | topLED 32 W 700 mA | CRI 90

8516

Double emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 126 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 4145 lm, with a 129.5 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of wood and features a white finish, processed by means of melamine; the diffuser is made of pe; the mounting frame is made of iron, with an embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 3.610 kg. The power supply driver is included in the delivery.

The total absorbed power is 32 W.


The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features

Luminous flux (source)	4145 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20



Square_SR | Ceiling Lights | Accessories
8516



Dimmer
PUSH DIM, 220-240V

Code
KIT0026



Dimmer
Bluetooth, 85-240V

Code
KIT0080