Entourage_P1




Pendant Luminaires | 220-240 V | 5xE27 **7671**











| Technical data | |
|--|------------------|
| Installation position | Ceiling |
| Installation environment | Indoor |
| Lamp cap | 5 x E27 Max 46W |
| Frequency | 50-60 Hz |
| Optics | General Lighting |
| Light emission direction | downward |
| Safety class | 1 |
| IP . | IP40 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Induzione | No |
| Emergency mode | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |

| Finishing casin | 3 | |
|--------------------------|-----------------|--|
| Material | PE | |
| Colour | rust | |
| Processing | Coating | |
| | | |
| Finishing diffus | er | |
| Material | PMMA | |
| Colour | opaline | |
| Processing | Satin finishing | |
| | | |
| Finishing mounting frame | | |
| Material | Iron | |
| Colour | corten | |
| Processing | Coating | |
| | | |

Entourage_P1



Pendant Luminaires | 220-240 V | 5xE27 **7671**

Single emission pendant luminaires for indoor application. Compatibility: LED lamp, compact fluo 30 W, halogen 46 W; lamp cap 5xE27.

The device body is made of pe and features a rust finish, processed by means of coating; the diffuser is made of pmma with a satin finishing treatment; the mounting frame is made of iron, with a corten finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 23.360 kg.

The device features protection class I and can be ceiling-mounted.

| Illuminotechnical Features | |
|----------------------------|--|
| 3500 lm | |
| 2800 K | |
| 100 Ra | |
| | |