
## Pendant Luminaires | 220-240 V | 5xE27 7669





• 🚽 📭 🗋 🔶

Technical data	
Installation position	Ceiling
Installation environment	Indoor
Lamp cap	5 x E27 Max 46W
Frequency	50-60 Hz
Optics	General Lighting
Light emission direction	downward
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Induzione	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing		
Material	PE	
Colour	Beton dark grey	
Processing	Coating	
Finishing diffus	er	
Material	PMMA	
Colour	opaline	
Processing	Satin finishing	
Finishing moun	ting frame	
Material	Iron	
Colour	embossed white RAL 9003	
Processing	Coating	

Pendant Luminaires | 220-240 V | 5xE27 7669

Single emission pendant luminaires for indoor application. Compatibility: LED lamp, compact fluo 30 W, halogen 46 W; lamp cap 5xE27.

The device body is made of pe and features a beton dark grey finish, processed by means of coating; the diffuser is made of pmma with a satin finishing treatment; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 23.360 kg.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features		
Luminous flux (source)	3500 lm	
Colour temperature	2500 K	
Colour rendering index	100 Ra	