

Product code	Color
265-250BN-73	White/black baffle

General Specifications

Product type	: Downlights
Mounting type	: Ceiling - recessed
Description	: Fixed downlight for both accent and diffused lighting, designed for COB LEDs, featuring a rearward optic for a high visual comfort. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. High protection rating IP66/20.
Indoor/outdoor lights	: Indoor
Applications	: Hospitality, Residential

Lighting specifications

Average lamp life (h)	: L80B10 50.000
Lamp description	: LED 1470lm 12W 3000K CRI90
Nominal lumens on thermal regime	: 1470
Efficiency L.O.R. (%)	: 56
Delivered lumens (lm)	: 824
Lamp wattage (W)	: 12
Color temperature (K)	: 3000

Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted
Reflector	: Mirror-metallized thermoplastic material
Closing Screen	: Clear thermoplastic material
Thermal Dissipation	: Passive

Electrical Specifications

Glow wire (°C)	: 850
Driver	: Separate item
Driver mounting	: Remote

Weight and Dimensions

Shape	: Round
External diameter (mm)	: 92
False ceiling thickness (mm)	: 1-30
Height (mm)	: 90
Cutout shape	: Round
Cutout Diameter (mm)	: 70
Recessed depth (mm)	: 90
Weight (Kg)	: 0.5

Optical Specifications

Aiming	: Fixed
Light distribution	: Symmetric
Light emission	: Direct
Light beam	: 26°
Note	: 45° (mirror metallized), 65° (white) optics are available on demand.
Unified Glare Rating (U.G.R.)	: <5

ACCESSORIES




Product Code : 28-3868-31
 Name : Professional optic device 65°
 Finish : White
 Beam : 65°
 Shape : Round



Product Code : 28-3868-51
 Name : Professional optic device 45°
 Finish : Mirror metallized
 Beam : 45°
 Shape : Round

Drivers



Product Code : 81-04003
 Name : Driver 350mA DALI dimmable

Lamps

	Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color temperature (K)	Color rendering (CRI)
	LED	COB LED	12	1470	3000	90