

Product code	Color
243-250BN-21	Mat white
243-250BN-52	Silver

### General Specifications

Product type	: Downlights
Mounting type	: Ceiling - recessed
Description	: Fixed downlight for diffused lighting designed for the last generation of COB LEDs. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP44.
Indoor/outdoor lights	: Indoor
Applications	: Accommodation facilities, Retail, Shopping centres, Showrooms

### Lighting specifications

Average lamp life (h)	: L80B10 50.000
Lamp description	: LED 4900lm 38W 3000K
Nominal lumens on thermal regime	: 4900
Efficiency L.O.R. (%)	: 86,0
Delivered lumens (lm)	: 4214
Lamp wattage (W)	: 38
Color temperature (K)	: 3000

### Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted
Reflector	: Mirror-metallized thermoplastic material
Closing Screen	: Tempered safety glass 4 mm
Thermal Dissipation	: Passive
Ring	: Die-cast aluminium polyester painted

### Electrical Specifications

Glow wire (°C)	: 850
Driver	: Separate item
Driver mounting	: Remote


### Weight and Dimensions

Shape	: Round
External diameter (mm)	: 140
False ceiling thickness (mm)	: 1-30
Height (mm)	: 140
Cutout shape	: Round
Cutout Diameter (mm)	: 126
Recessed depth (mm)	: 150
Weight (Kg)	: 0.7


### Optical Specifications

Aiming	: Fixed
Light distribution	: Symmetric
Light emission	: Direct
Light beam	: 60°

## ACCESSORIES




Product Code : 28-3403-21/52  
 Name : Square frame with clear glass  
 Finish : Polyester painted  
 Shape : Square




Product Code : 98-13380-61  
 Name : Sandblasted glass  
 Shape : Round

## Drivers



Product Code : 81-04014  
 Name : Driver 1050mA DALI dimmable  
 description : Driver 1050mA DALI dimmable.&nbsp;

## Lamps

	Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color temperature (K)	Color rendering (CRI)
	LED	COB LED	38	4900	3000	85

## Pictures and Applications

