

Product code	Color
265-250BN-73	White/black baffle

General Specifications

Product type	: Downlights
Mounting type	: Ceiling - recessed
Description	: Fixed downlight for both accent and diffused lighting, designed for COB LEDs, featuring a rearward optic for a high visual comfort. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. High protection rating IP66/20.

Indoor/outdoor lights	: Indoor
Applications	: Hospitality, Residential

Lighting specifications

Average lamp life (h)	: L80B10 50.000
Lamp description	: LED 800lm 6W 3000K CRI 90
Nominal lumens on thermal regime	: 800
Efficiency L.O.R. (%)	: 56
Delivered lumens (lm)	: 448
Lamp wattage (W)	: 6
Color temperature (K)	: 3000

Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted
Reflector	: Mirror-metallized thermoplastic material
Closing Screen	: Clear thermoplastic material
Thermal Dissipation	: Passive

Electrical Specifications



Glow wire (°C)	: 850
Driver	: Separate item
Driver mounting	: Remote

Weight and Dimensions

Shape	: Round
External diameter (mm)	: 92
False ceiling thickness (mm)	: 1-30
Height (mm)	: 90
Cutout shape	: Round
Cutout Diameter (mm)	: 70
Recessed depth (mm)	: 90
Weight (Kg)	: 0.5

Optical Specifications

Aiming	: Fixed
Light distribution	: Symmetric
Light emission	: Direct
Light beam	: 26°
Note	: 45° (mirror metallized), 65° (white) optics are available on demand.
Unified Glare Rating (U.G.R.)	: <5



ACCESSORIES




Product Code : 28-3868-31
 Name : Professional optic device 65°
 Finish : White
 Beam : 65°
 Shape : Round




Product Code : 28-3868-51
 Name : Professional optic device 45°
 Finish : Mirror metallized
 Beam : 45°
 Shape : Round

Drivers



Product Code : 81-04023
 Name : Driver 180mA dimmable on the mains and 1-10V

Lamps

	Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color temperature (K)	Color rendering (CRI)
	LED	COB LED	6	800	3000	90