

| | |
|---------------------|--------------------|
| Product code | Color |
| 265-250BN-73 | White/black baffle |

General Specifications

| | |
|---------------|--|
| Product type | : Downlights |
| Mounting type | : Ceiling - recessed |
| Description | : Fixed downlight for both accent and diffused lighting, designed for COB LEDs, featuring a rearward optic for a high visual comfort. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. High protection rating IP66/20. |

| | |
|-----------------------|----------------------------|
| Indoor/outdoor lights | : Indoor |
| Applications | : Hospitality, Residential |

Lighting specifications

| | |
|----------------------------------|-----------------------------|
| Average lamp life (h) | : L80B10 50.000 |
| Lamp description | : LED 1090lm 9W 3000K CRI90 |
| Nominal lumens on thermal regime | : 1090 |
| Efficiency L.O.R. (%) | : 56 |
| Delivered lumens (lm) | : 611 |
| Lamp wattage (W) | : 9 |
| Color temperature (K) | : 3000 |

Physical Specifications

| | |
|---------------------|--|
| Body | : Die-cast aluminium |
| Finishes | : Polyester painted |
| Reflector | : Mirror-metallized thermoplastic material |
| Closing Screen | : Clear thermoplastic material |
| Thermal Dissipation | : Passive |

Electrical Specifications



| | |
|-----------------|-----------------|
| Glow wire (°C) | : 850 |
| Driver | : Separate item |
| Driver mounting | : Remote |

Weight and Dimensions

| | |
|------------------------------|---------|
| Shape | : Round |
| External diameter (mm) | : 92 |
| False ceiling thickness (mm) | : 1-30 |
| Height (mm) | : 90 |
| Cutout shape | : Round |
| Cutout Diameter (mm) | : 70 |
| Recessed depth (mm) | : 90 |
| Weight (Kg) | : 0.5 |

Optical Specifications

| | |
|-------------------------------|--|
| Aiming | : Fixed |
| Light distribution | : Symmetric |
| Light emission | : Direct |
| Light beam | : 26° |
| Note | : 45° (mirror metallized), 65° (white) optics are available on demand. |
| Unified Glare Rating (U.G.R.) | : <5 |



ACCESSORIES




Product Code : 28-3868-31
 Name : Professional optic device 65°
 Finish : White
 Beam : 65°
 Shape : Round




Product Code : 28-3868-51
 Name : Professional optic device 45°
 Finish : Mirror metallized
 Beam : 45°
 Shape : Round

Drivers



Product Code : 81-04009
 Name : Driver 250mA

Lamps

| | Lamp categories | Lamp type | Lamp wattage (W) | Nominal lumens on thermal regime (lm) | Color temperature (K) | Color rendering (CRI) |
|--|-----------------|-----------|------------------|---------------------------------------|-----------------------|-----------------------|
|  | LED | COB LED | 9 | 1090 | 3000 | 90 |