




Pendant Luminaires | 220-240 V | 1xE27
90226



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Lamp cap	1 x E27 Max 57W
Frequency	50-60 Hz
Optics	General Lighting
Light emission direction	downward
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	2.400 Kg

Finishing casing	
Material	Iron
Colour	white
Processing	Coating
Finishing diffuser	
Material	Glass - Glass
Colour	white - lilac
Processing	Silk-screening - Silk-screening



Pendant Luminaires | 220-240 V | 1xE27
90226

Double emission pendant luminaires for indoor application. Compatibility:
LED lamp, compact fluo 30 W, halogen 57 W; lamp cap 1xE27.

The device body is made of iron and features a white finish, processed by means of coating; the diffuser is made of glass with a silk-screening treatment; the diffuser is made of glass with a silk-screening treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 2.400 kg.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	915 lm
Colour temperature	2500 K
Colour rendering index	100 Ra