


# Oh!\_S65



Ceiling Lights | 220-240 V | topLED 20 W 500 mA | CRI 90  
**15109**



Ø 550

Technical data	
Type	Surface
Installation position	Wall lights - Ceiling
Installation environment	Outdoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	20 W
Luminous flux (source)	2652 lm
Frequency	50 - 60 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
IP	IP65
IK	IK10
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	4.9 Kg

Finishing diffuser	
Material	PE
Colour	neutral

Ceiling Lights | 220-240 V | topLED 20 W 500 mA | CRI 90  
**15109**

Double emission ceiling lights for outdoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2652 lm, with a 132.6 lm/W nominal luminous efficacy.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 4.9 kg.

The total absorbed power is 20 W.

and can be wall lights or ceiling-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	79 %
Luminous flux (source)	2652 lm
Luminaire luminous flux	2115 lm
Consumption	20 W
Luminaire efficacy	105 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra

UGR	
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 19
UGR axial	< 16

OPTICAL	
Light distribution simmetry	Symmetrical
C0/C180 optics	180°

