Oh!_Mars

Floor Lamp | 220-240 V | 1xE27 15131



Installation positionFloorInstallation environmentOutdoorLamp cap1 x E27 Max 46WFrequency50-60 HzOpticsGeneral LightingLight emission directionupwardSafety class2IPIP65IKIK06Glow wire test650°Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoDirectonalNoDirectonalNoDirectonalNoDirectoreNoDirectoreNoEttlingNoEttlingNoSafely classSingle emissionTiltingNoNoSingle emission	Technical data				
Installation environmentOutdoorLamp cap1 x E27 Max 46WFrequency50-60 HzOpticsGeneral LightingLight emission directionupwardSafety class2IPIP65IKIK06Glow wire test650°Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoDirectonalNoDirectonalNoDirectonalNoDirectoreNoDirectoreNoDirectoreNoDirectoreNoDirectoreNoEttingNoTiltingNoCable includedYesCable length5 mElectric socketType FResin pottingNoType of light emissionSingle emission	Туре	Floor Lamp			
Lamp cap1 x E27 Max 46WFrequency50-60 HzOpticsGeneral LightingLight emission directionupwardSafety class2IPIP65IKIK06Glow wire test650°Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoDirectionalNoDirectionalNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoEttingNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelNoDirectorelSimpleDirectorelSingle emissionType of light emissionSingle emission	Installation position	Floor			
Lamp capS0-60 HzPrequency50-60 HzOpticsGeneral LightingLight emission directionupwardSafety class2IPIP65IKIK06Glow wire test650°Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoEmergency modeNoDirectionalNoTiltingNoDrive-overNoCable includedYesCable length5 mElectric socketType FResin pottingNoType of light emissionSingle emission	Installation environment	Outdoor			
OpticsGeneral LightingLight emission directionupwardSafety class2IPIP65IKIK06Glow wire test650°Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoEmergency modeNoDirectionalNoTiltingNoWalk-overNoDrive-overNoCable includedYesCable length5 mElectric socketType FResin pottingNoType of light emissionSingle emission	Lamp cap	1 x E27 Max 46W			
Light emission directionupwardSafety class2IPIP65IKIK06Glow wire test650°Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoEmergency modeNoDirectionalNoTiltingNoOrive-overNoCable includedYesCable length5 mElectric socketType FResin pottingNoType of light emissionSingle emission	Frequency	50-60 Hz			
Safety class2IPIP65IKIK06Glow wire test650°Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoEmergency modeNoDirectionalNoTiltingNoWalk-overNoDrive-overNoCable includedYesCable length5 mElectric socketType FResin pottingNoType of light emissionSingle emission	Optics	General Lighting			
IPIP65IKIK06Glow wire test650°Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoEmergency modeNoDirectionalNoTiltingNoWalk-overNoDrive-overNoCable includedYesCable length5 mElectric socketType FResin pottingNoType of light emissionSingle emission	Light emission direction	upward			
IKIK06Glow wire test650°Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoEmergency modeNoDirectionalNoTiltingNoWalk-overNoDrive-overNoCable includedYesCable length5 mElectric socketType FResin pottingNoType of light emissionSingle emission	Safety class	2			
Glow wire test650°Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoEmergency modeNoDirectionalNoTiltingNoWalk-overNoDrive-overNoCable includedYesCable length5 mElectric socketType FResin pottingNoType of light emissionSingle emission	IP	IP65			
Direct mounting on normally flammable surfacesYesCEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoEmergency modeNoDirectionalNoTiltingNoWalk-overNoDrive-overNoCable includedYesCable length5 mElectric socketType FResin pottingNoType of light emissionSingle emission	IK	IK06			
CEYesETLNoFire Rated (BS 476 PT21 compliant)NoInductionNoInductionNoEmergency modeNoDirectionalNoTiltingNoWalk-overNoDrive-overNoCable includedYesCable length5 mElectric socketType FResin pottingNoType of light emissionSingle emission	Glow wire test	650°			
ETL No Fire Rated (BS 476 PT21 compliant) No Induction No Induction No Emergency mode No Directional No Tilting No Walk-over No Drive-over No Cable included Yes Cable length 5 m Electric socket Type F Resin potting No Type of light emission Single emission	Direct mounting on normally flammable surfaces	Yes			
Fire Rated (BS 476 PT21 compliant) No Induction No Emergency mode No Directional No Tilting No Walk-over No Drive-over No Cable included Yes Cable length 5 m Electric socket Type F Resin potting No Type of light emission Single emission	CE	Yes			
Induction No Emergency mode No Directional No Tilting No Walk-over No Drive-over No Cable included Yes Cable length 5 m Electric socket Type F Resin potting No Type of light emission Single emission	ETL	No			
Emergency mode No Directional No Tilting No Walk-over No Drive-over No Cable included Yes Cable length 5 m Electric socket Type F Resin potting No Type of light emission Single emission	Fire Rated (BS 476 PT21 compliant)	No			
Directional No Tilting No Walk-over No Drive-over No Cable included Yes Cable length 5 m Electric socket Type F Resin potting No Type of light emission Single emission	Induction	No			
Tilting No Walk-over No Drive-over No Cable included Yes Cable length 5 m Electric socket Type F Resin potting No Type of light emission Single emission	Emergency mode	No			
Walk-over No Drive-over No Cable included Yes Cable length 5 m Electric socket Type F Resin potting No Type of light emission Single emission	Directional	No			
Drive-over No Cable included Yes Cable length 5 m Electric socket Type F Resin potting No Type of light emission Single emission	Tilting	No			
Cable included Yes Cable length 5 m Electric socket Type F Resin potting No Type of light emission Single emission	Walk-over	No			
Cable length 5 m Electric socket Type F Resin potting No Type of light emission Single emission	Drive-over	No			
Electric socket Type F Resin potting No Type of light emission Single emission	able included Yes				
Resin potting No Type of light emission Single emission	Cable length	5 m			
Type of light emission Single emission	Electric socket	Type F			
	Resin potting	No			
Net weight 2.000 Kg	Type of light emission	Single emission			
	Net weight	2.000 Kg			





Finishing diffuser

Material	PE	
Colour	Wood	

Oh!_Mars

Floor Lamp | 220-240 V | 1xE27 15131

Single emission floor lamp for outdoor application. Compatibility: LED lamp, halogen 46 W, compact fluo 20 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 2.000 kg.

. The power supply cable is included and features.

The device features protection class II and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Illuminotechnical Features		
Luminous flux (source)	700 lm	
Colour temperature	2800 K	
Colour rendering index	100 Ra	

Oh!_Mars

Oh!_Mars | Floor Lamp | Accessories 15131

	22 0 11	Outer casing - outer casing for installation on ground or on concrete	Code 14930
T T T T	30 1 3 0 13	Pegs	Code 14931
	6 <u> </u>	anti-theft - anti-theft ground fixing bracket	Code 14080