




| RGB
15165



Technical data	
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optics	General Lighting
Power	18 W
Current intensity	500mA
CCT / Tone	RGB
C.C. / C.V.	CC
Safety class	3
IP	IP65
IK	IK10
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	No
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	7.940 Kg

Finishing diffuser

Material	PE
Colour	neutral

Electronics



99140
N/O button Multi Channel and Power 3ch. 190~250V
AC / 180~275V DC




| RGB
15165

Double emission floor lamp for outdoor application. The RGB LED light source with a general lighting light distribution is composed of 1 powerleds LEDs.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 7.940 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 18 W.

The device features protection class III and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).




Outer casing - outer casing for installation on ground or on concrete

Code
14930



Pegs - peg for ground mounting

Code
14937



anti-theft - anti-theft ground fixing bracket

Code
14082