## Wall Lights | 220-240 V | 1xG5 3696





ℜ ♥ ± □ □20 □ ○

Technical data	
Туре	Surface
Installation position	Wall lights
Installation environment	Indoor
Power	1 x 24 W
Lamp cap	1 x G5
Frequency	50 - 60 Hz
Optics	General Lighting
Light emission direction	downward
Safety class	1
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	1.570 Kg

Finishing casing			
Material	Iron		
Colour	chrome		
Processing	Electroplating		
Finishing diffus	۶ <b>۲</b>		
Material	PMMA		

Material	PMMA	
Colour	white	
Processing	Satin finishing	

Single emission wall lights for indoor application. Fluorescent lamp included 24W, lamp cap 1xG5.

The device body is made of iron and features a chrome finish, processed by means of electroplating; the diffuser is made of pmma with a satin finishing treatment; the mounting frame is made of iron, with a chrome finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 1.570 kg.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features		
Luminous flux (source)	2000 lm	
Colour temperature	3000 K	
Colour rendering index	80 Ra	