Oh!_FL65

Floor Lamp | 1 x powerLEDs 24 W 500 mA | RGB 15167



Technical data		
Туре	Floor Lamp	
Installation position	Floor	
Installation environment	Outdoor	
Light Source	LED	
Optics	General Lighting	
Power	24 W	
Current intensity	500mA	
CCT / Tone	RGB	
C.C. / C.V.	CC	
Safety class	3	
IP	IP65	
К	IK10	
Glow wire test	650°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Fire Rated (BS 476 PT21 compliant)	No	
Driver included	No	
Induction	No	
Emergency mode	No	
Motion sensor	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Double emission	
Net weight	17.640 Kg	

🕅 🕼 C.C. 🎘 IK10 IP65 🛄 🏠



Finishing diffuser

PE

neutral

Material

Colour

Electronics



99140 N/O button Multi Channel and Power 3ch. 190~250V AC / 180~275V DC

Oh!_FL65

Floor Lamp | 1 x powerLEDs 24 W 500 mA | RGB 15167

Double emission floor lamp for outdoor application. The RGB LED light source with a general lighting light distribution is composed of 1 powerleds LEDs.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 17.640 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 24 W.

The device features protection class III and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Oh!_FL65

Oh!_FL65 | Floor Lamp | Accessories 15167

	22 0 11	Outer casing - outer casing for installation on ground or on concrete	Code 14930
	50 0 13	Pegs - peg for ground mounting	Code 14937
7///	3 0 42 0 42	anti-theft - anti-theft ground fixing bracket	Code 14083