



Floor Lamp | 220-240 V | 1xE27
15130



Technical data	
Type	Floor Lamp
Installation position	Floor
Installation environment	Outdoor
Lamp cap	1 x E27 Max 30W
Frequency	50-60 Hz
Optics	General Lighting
Safety class	2
IP	IP65
IK	IK10
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	5 m
Electric socket	Type F
Resin potting	No
Type of light emission	Double emission
Net weight	1.300 Kg

Finishing diffuser	
Material	PE
Colour	Wood



Floor Lamp | 220-240 V | 1xE27
15130

Double emission floor lamp for outdoor application. Compatibility: LED lamp, halogen 30 W, compact fluo 14 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 1.300 kg.

. The power supply cable is included and features.


The device features protection class II and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Illuminotechnical Features	
Luminous flux (source)	405 lm
Colour temperature	2800 K
Colour rendering index	100 Ra



Outer casing - outer casing for installation on ground or on concrete

Code
14930



Pegs

Code
14931