

Product code	Color
239-239BN-21	Mat white

General Specifications

Product type	: Downlights
Mounting type	: Ceiling - recessed
Description	: Recessed adjustable downlight, designed for the last generation of COB LEDs, with a shallow depth. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Low glare level: UGR < 15.
Indoor/outdoor lights	: Indoor
Applications	: Accommodation facilities, Conference rooms, Hotels, Offices, Residential, Shopping centres, Showrooms

Lighting specifications

Average lamp life (h)	: L80B10 50.000
Lamp description	: LED 700lm 8.5W 3000K
Nominal lumens on thermal regime	: 700
Efficiency L.O.R. (%)	: 91
Delivered lumens (lm)	: 638
Lamp wattage (W)	: 8.5
Color temperature (K)	: 3000

Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted
Closing Screen	: Clear polycarbonate
Thermal Dissipation	: Passive

Electrical Specifications

Glow wire (°C)	: 850
Driver	: Separate item
Driver mounting	: Remote

Weight and Dimensions

Shape	: Round
External diameter (mm)	: 95
False ceiling thickness (mm)	: 1-30
Height (mm)	: 56
Cutout shape	: Round
Cutout Diameter (mm)	: 86
Recessed depth (mm)	: 56
Weight (Kg)	: 0.4

Optical Specifications

Aiming	: Adjustable
Light distribution	: Symmetric
Light emission	: Direct
Light beam	: 26°
Horizontal orientation	: +/- 20°
Note	: 45° (mirror metallized), 65° (white) optics are available on demand.
Unified Glare Rating (U.G.R.)	: <15

ACCESSORIES




Product Code : 28-3868-31
 Name : Professional optic device 65°
 Finish : White
 Beam : 65°
 Shape : Round




Product Code : 28-3868-51
 Name : Professional optic device 45°
 Finish : Mirror metallized
 Beam : 45°
 Shape : Round

Drivers



Product Code : 81-04008
 Name : Driver 500mA dimmable on the mains and 1-10V

Lamps	Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color rendering (CRI)
	LED	COB LED	8.5	700	90

Pictures and Applications

