


## 5STARS 1000 A/I




<b>Part number</b>	04016794
<b>Lampholder:</b>	E40
<b>Light Source:</b>	METAL HALIDE LAMPS
<b>Wattage:</b>	1x1000 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP 66
<b>IK-J-xxIP:</b>	IK08 5J xx5
<b>Optic:</b>	ASYMMETRIC INTENSIVE REFLECTOR
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	40°




### Description

- Discharge lamp floodlight for indoor and outdoor lighting, comprising:
- Polyester powder coated die-cast aluminium housing
  - Flat tempered glass diffuser
  - Polished aluminium asymmetrical reflector
  - Gaskets made of silicone foam directly applied on glass without joints
  - Electrical wiring box with ignitor, supplied with the luminaire, made of technopolymer reinforced with glass fibre
  - Stainless steel external screws
  - Fully integrated stainless steel aluminium spring clips
  - Powder coated steel bracket
  - Lamp holder box constructed of technopolymer
  - Graduated goniometer for aiming purposes
  - Patented anti-vacuum device
  - Adequate power supply units, available as accessories, must be used for all floodlights

### PHOTOMETRIC DATA



### TECHNICAL DRAWINGS



## 5STARS 1000 HPI-T



14013220  
Aluminium power supply unit IP65, 230 V - 50 Hz, class I, for lamp 1000 W HPI-T with fuse and without ignitor




14216003  
Power supply unit with aluminium base and polyamide cover IP65, 230 V - 50 Hz, class I, for 1000 W HPI-T lamps with fuse and without ignitor



14025701  
Power supply unit 230 V - 50 Hz, class I, on galvanised steel plate for 1000 W HPI-T lamps with fuse and without ignitor

## 5STARS 1000 A



14070620  
Steel wire lamp steady support (recommended for use in installations subject to heavy vibration) (5STARS 2/A).

## 5STARS 1000




14026520  
5STARS 2 frosted glass, optional replacement for standard clear glass.



14012320  
External anti-glare louvre painted aluminium grey.



14012420  
External cowl painted aluminium grey.



14012520  
Steel galvanised wire guard (18 Joule).



14012620  
Single 5STARS 2 pole top fitting and outreach arm for Ø60-76mm poles.



14012720  
Twin 5STARS 2 pole top fitting and outreach arm for Ø60-76mm poles.



14011594  
1000mm extension arm in heavy gauge steel painted aluminium grey.



14044620  
5STARS 2 strengthening bracket. Designed for single point fixing M12-M14 screw in centre of the bracket.