

## 5STARS 1 CA/M



<b>Part number</b>	05086194
<b>Lampholder:</b>	G12
<b>Light Source:</b>	METAL HALIDE LAMPS
<b>Wattage:</b>	1x70 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP 66
<b>IK-J-xxIP:</b>	IK08 7J xx5
<b>Power factor:</b>	COSφ ≥ 0,9
<b>Optic:</b>	ASYMMETRIC MEDIUM CIRCLE REFLECTOR
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	30°




### Description


Discharge lamp floodlight for indoor and outdoor lighting, comprising:

- Polyester powder coated die-cast aluminium housing
- Flat tempered glass diffuser
- Polished aluminium asymmetrical reflector
- Anti-ageing silicone gasket
- Fully integrated technopolymer trim hinged to the housing
- Waterproof cable gland M16x1.5 for cables Ø 5- Ø 10 mm
- Stainless steel external screws
- Powder coated steel bracket

### PHOTOMETRIC DATA



### TECHNICAL DRAWINGS



## 5STARS 1



14029094

Gliding support made of painted aluminium for the installation on 60 - 76 mm diam. posts . 1 luminaire 5STARS 1 / WIN+1.



14047194

Gliding support made of painted aluminium for the installation on 60- 76 mm diam. posts 2 opposed luminaires 5STARS 1 / WIN+1.