





Wall Lights | 220-240 V | arrayLED 6.5 W 350 mA | CRI 80
64512W94



Technical data	
Type	Surface
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Light emission direction	downward and upward
Power	6.5 W
Source lumens	876 lm
Frequency	50 - 60 Hz
CCT / Tone	3000 K
Colour rendering index	80 Ra
AC / DC	DC
Safety class	2
IP	IP40
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Operating temperature	-20°C / +50°C
Driver included	Driver
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	0.51 Kg

Finishing casing	
Material	Aluminium
Colour	grey RAL 9006
Processing	Coating

Finishing diffuser	
Material	Glass
Colour	black
Processing	Silk-screening



Wall Lights | 220-240 V | arrayLED 6.5 W 350 mA | CRI 80
64512W94

Double emission wall lights for indoor application. The warm white LED light source is composed of 2 arrayed LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 876 lm, with a 134.8 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a grey ral 9006 finish, processed by means of coating; the diffuser is made of glass with a silk-screening treatment. The ingress protection degree is IP40; the total weight is of 0.51 kg.

The total absorbed power is 6.5 W.

The device features protection class II and can be wall lights-mounted.

Illuminotechnical Features

Source lumens	876 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	80 Ra
Gamut Area Index	55 GAI
Colour Rendering Index	10 R9
IES TM-30 Rf	83
IES TM-30 Rg	96
Black Body Locus	On

LED Life / Failure Ratio

L70 B10 C0 296940h (at Tj 65 °C Ta 25 °C)