

## Floor Lamp | 220-240 V | 1xE27 10110



Installation position	Technical data	
Installation environment  Lamp cap  Frequency  Optics  General Lighting Light emission direction  Safety class  IP  IP20  IK  IK10  Glow wire test  Direct mounting on normally flammable surfaces  CE  Yes  ETL  No  Fire Rated (BS 476 PT21 compliant)  Induction  Mo  Motion sensor  No  Directional  Tilting  No  Walk-over  Drive-over  Cable length  Cable length  Light emission direction  So-60 Hz  General Lighting  Upward  Seneral Lighting  No  IK10  IN10  IN20  IN41  IN50  IN61  IN61	Туре	Floor Lamp
1 x E27 Max 77W	Installation position	Floor
Electric socket   Supplementary   Supplement	Installation environment	Indoor
Optics General Lighting Light emission direction upward  Safety class 2 IP IP20 IIK IK10 Glow wire test 650° Direct mounting on normally flammable surfaces Yes CE Yes ETL No Fire Rated (BS 476 PT21 compliant) No Induction No Emergency mode No Motion sensor No Directional No Tilting No Walk-over No Drive-over No Cable included Yes Cable length 2 m Electric socket Tp20	Lamp cap	1 x E27 Max 77W
Light emission direction upward  Safety class 2  IP IP20  IK IK10  Glow wire test 650°  Direct mounting on normally flammable surfaces Yes  CE Yes  ETL No  Fire Rated (BS 476 PT21 compliant) No  Induction No  Emergency mode No  Motion sensor No  Directional No  Tilting No  Walk-over No  Drive-over No  Cable included Yes  Cable length 2 m  Electric socket Type C	Frequency	50-60 Hz
Safety class         2           IP         IP20           IK         IK10           Glow wire test         650°           Direct mounting on normally flammable surfaces         Yes           CE         Yes           ETL         No           Fire Rated (BS 476 PT21 compliant)         No           Induction         No           Emergency mode         No           Motion sensor         No           Directional         No           Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	Optics	General Lighting
IP20	Light emission direction	upward
IK	Safety class	2
Glow wire test         650°           Direct mounting on normally flammable surfaces         Yes           CE         Yes           ETL         No           Fire Rated (BS 476 PT21 compliant)         No           Induction         No           Emergency mode         No           Motion sensor         No           Directional         No           Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	IP	IP20
Direct mounting on normally flammable surfaces         Yes           CE         Yes           ETL         No           Fire Rated (BS 476 PT21 compliant)         No           Induction         No           Emergency mode         No           Motion sensor         No           Directional         No           Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	IK	IK10
CE         Yes           ETL         No           Fire Rated (BS 476 PT21 compliant)         No           Induction         No           Emergency mode         No           Motion sensor         No           Directional         No           Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	Glow wire test	650°
ETL         No           Fire Rated (BS 476 PT21 compliant)         No           Induction         No           Emergency mode         No           Motion sensor         No           Directional         No           Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	Direct mounting on normally flammable surfaces	Yes
Fire Rated (BS 476 PT21 compliant)         No           Induction         No           Emergency mode         No           Motion sensor         No           Directional         No           Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	CE	Yes
Induction         No           Emergency mode         No           Motion sensor         No           Directional         No           Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	ETL	No
Emergency mode         No           Motion sensor         No           Directional         No           Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	Fire Rated (BS 476 PT21 compliant)	No
Motion sensor         No           Directional         No           Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	Induction	No
Directional         No           Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	Emergency mode	No
Tilting         No           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	Motion sensor	No
Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type C	Directional	No
Drive-over No Cable included Yes Cable length 2 m Electric socket Type C	Tilting	No
Cable included Yes Cable length 2 m Electric socket Type C	Walk-over	No
Cable length 2 m  Electric socket Type C	Drive-over	No
Electric socket Type C	Cable included	Yes
	Cable length	2 m
Design potting	Electric socket	Type C
resin poung No	Resin potting	No
Type of light emission Single emission	Type of light emission	Single emission
Net weight 16.375 Kg	Net weight	16.375 Kg
















Finishing diffuser		
Material	PE	
Colour	neutral	



## Floor Lamp | 220-240 V | 1xE27 10110

Single emission floor lamp for indoor application. Compatibility: LED lamp, compact fluo 30 W, halogen 77 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP20; the total weight is of 16.375 kg.

. The power supply cable is included and features.

The device features protection class II and can be floor-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	77 %
Luminous flux (source)	1320 lm
Luminaire luminous flux	1028 lm
Consumption	77 W
Luminaire efficacy	17 lm/W
Colour rendering index	100 Ra

OPTICAL	
Light distribution simmetry	Symmetrical
C0/C180 optics	180°

