
Floor Lamp | 220-240 V | 1xE27 15162



Technical data		
Туре	Floor Lamp	
Installation position	Floor	
Installation environment	Outdoor	
Lamp cap	1 x E27 Max 46W	
Frequency	50-60 Hz	
Optics	General Lighting	
Light emission direction	upward	
Safety class	2	
IP	IP65	
к	IK10	
Glow wire test	650°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Fire Rated (BS 476 PT21 compliant)	No	
Induction	No	
Emergency mode	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	5 m	
Electric socket	Type F	
Resin potting	No	
Type of light emission	Single emission	
Net weight 4.200 Kg		





Finishing diffuser

Material Colour PE neutral

Floor Lamp | 220-240 V | 1xE27 15162


Single emission floor lamp for outdoor application. Compatibility: LED lamp, halogen 46 W, compact fluo 30 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 4.200 kg.

. The power supply cable is included and features.

The device features protection class II and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Illuminotechnical Features		
Light Output Ratio (LOR)	77 %	
Luminous flux (source)	700 lm	
Luminaire luminous flux	1480 lm	
Consumption	30 W	
Luminaire efficacy	63 lm/W	
Colour rendering index	100 Ra	
OPTICAL		
Light distribution simmetry	Symmetrical	
C0/C180 optics	180°	



Oh!_FL65

Oh!_FL65 | Floor Lamp | Accessories 15162

N	22 0 11	Outer casing - outer casing for installation on ground or on concrete	Code 14930
	30 0 13	Pegs	Code 14931
71111	034	anti-theft - anti-theft ground fixing bracket	Code 14081
		Connector	Code 14992