




Table Lamps | topLED 5 W 150 mA | CRI 80
7243



| Technical data | |
|--|------------------|
| Type | Table Lamps |
| Installation position | Floor |
| Installation environment | Indoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | downward |
| Power | 5 W |
| Source lumens | 400 lm |
| Frequency | 50-60 Hz |
| CCT / Tone | 3000 K |
| Colour rendering index | 80 Ra |
| Safety class | 2 |
| IP | IP20 |
| Optical compartment IP | IP40 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Fire Rated (BS 476 PT21 compliant) | No |
| Induction | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Double emission |
| Net weight | 0.900 Kg |
| Electrostatic discharge protection | No |
| Surge protection | No |

Finishing diffuser

| | |
|------------|---------|
| Material | Glass |
| Colour | white |
| Processing | Coating |

Electronics

012000395000
Controller

Table Lamps | topLED 5 W 150 mA | CRI 80 7243

Double emission table lamps for indoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 400 lm, with a 80.0 lm/W nominal luminous efficacy.

The diffuser is made of glass with a coating treatment; the mounting frame is made of PC, with a white finish, processed by means of satin finishing. The ingress protection degree is IP20; the total weight is of 0.900 kg.

The total absorbed power is 5 W.

The device features protection class II and can be floor-mounted.

| Illuminotechnical Features | |
|---------------------------------------|----------------|
| Light Output Ratio (LOR) | 58 % |
| Source lumens | 400 lm |
| Delivered lumens | 235 lm |
| Consumption | 5.5 W |
| Luminaire efficacy | 44 lm/W |
| Colour temperature | 3000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 80 Ra |
| LED Life / Failure Ratio | |
| L70 B20 C0 72.5h | |

| OPTICAL | |
|-----------------------------|-------------|
| Light distribution simmetry | Symmetrical |
| C0/C180 optics | 180° |

