
Gluèd_PQ2

Pendant Luminaires | 220-240 V | 2xE27 4899





Technical data		
 Туре	Surface	
Installation position	Ceiling	
Installation environment	Indoor	
Lamp cap	2 x E27 Max 57W	
Frequency	50-60 Hz	
Optics	General Lighting	
Light emission direction	downward	
Safety class	1	
IP	IP20	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Fire Rated (BS 476 PT21 compliant)	No	
Induction	No	
Motion sensor	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Net weight	3.900 Kg	

Finishing casing				
Material	Iron			
Colour	white			
Processing	Coating			

Finishing diffuser				
Material	Glass			
Colour	white			
Processing	Silk-screening			

Pendant Luminaires | 220-240 V | 2xE27 4899

Double emission pendant luminaires for indoor application. Compatibility: LED lamp, halogen 57 W, compact fluo 20 W; lamp cap 2xE27.

The device body is made of iron and features a white finish, processed by means of coating; the diffuser is made of glass with a silk-screening treatment; the mounting frame is made of iron, with a grey ral 9006 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 3.900 kg.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features		
Source lumens	1830 lm	
Colour temperature	2500 K	
Colour rendering index	100 Ra	

2/2