




Floor Lamp | 220-240 V | topLED 26 W 1000 mA | CRI 90  
7100



### Technical data

Installation position	Floor
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	26 W
Luminous flux (source)	1871 lm
Frequency	50 - 60 Hz
CCT / Tonaltà	3000 K
Colour rendering index	90 Ra
AC / DC	AC-DC
Safety class	2
IP	IP40
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	Touch
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1.50 m
Electric socket	Type C
Resin potting	No

### Finishing casing

Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating

### Finishing diffuser

Material	PC
Colour	opaline

Floor Lamp | 220-240 V | topLED 26 W 1000 mA | CRI 90  
7100

Double emission floor lamp for indoor application. The warm white LED light source with a general lighting light distribution is composed of 105 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1871 lm, with a 72.0 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of PC. The ingress protection degree is IP40; the total weight is of 8.25 kg. The power supply driver is included in the delivery.

The total absorbed power is 26 W. The power supply cable is included and features.

The device features protection class II and can be floor-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	47 %
Luminous flux (source)	1871 lm
Luminaire luminous flux	897 lm
Consumption	26 W
Luminaire efficacy	34 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20

OPTICAL	
Light distribution simmetry	Asymmetrical
Optica C90/C270	109°

