Cupolè_P

Pendant Luminaires | 220-240 V | 1xE27 6383



max 160		18
	ø29	I

Finishing casing

Technical data		
Installation position	Ceiling	
Installation environment	Indoor	
Lamp cap	1 x E27 Max	
Frequency	50-60 Hz	
Optics	General Lighting	
Light emission direction	downward	
Safety class	1	
IP	IP20	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Induzione	No	
Emergency mode	No	
Motion sensor	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	

-	=
Material	Iron
Colour	nickel
Processing	Electroplating
Finishing diffus	er
Material	Glass
Colour	white
Processing	Coating
Finishing moun	ting frame
Material	Iron
Colour	black RAL 9005
Processing	Coating

Double emission pendant luminaires for indoor application. Compatibility: LED lamp, compact fluo 30 W, halogen 116 W; lamp cap 1xE27.

The device body is made of iron and features a nickel finish, processed by means of electroplating; the diffuser is made of glass with a coating treatment; the mounting frame is made of iron, with a black ral 9005 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 2.205 kg.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features			
Luminous flux (source)	2135 lm		
Colour temperature	2800 K		
Colour rendering index	100 Ra		