Ceiling Lights | 220-240 V | 2xGU5,3 6361





Technical data	
Туре	Semi-recessed
Installation position	Ceiling
Installation environment	Indoor
Lamp cap	2 x GU5,3 Max 50W
Optics	spot
Light emission direction	downward
Safety class	3
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Induction	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Net weight	0.790 Kg

Finishing diffuser	
Material	Glass

transparent

Colour

Electronics

2 x KIT86 Controller Single emission ceiling lights for indoor application. Compatibility: LED lamp, low-voltage halogen 50 W; lamp cap 2xGU5,3.

The diffuser is made of glass; the mounting frame is made of aluminium, with a chrome finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 0.790 kg. The power supply driver is not provided and is to be ordered separately.

The device features protection class III and can be ceiling-mounted, with a 65 mm diameter hole (in plasterboard).

Illuminotechnical Features	
Colour temperature	3100 K
Colour rendering index	100 Ra