Wall Lights | 220-240 V | topLED 20 W 900 mA | CRI 90 **90323**





	450	
80		
40 [

Technical data	
Туре	Surface
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	20 W
Source lumens	2135 lm
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
Safety class	1
IP .	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission

Metal_W



Wall Lights | 220-240 V | topLED 20 W 900 mA | CRI 90 90323

Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 24 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2135 lm, with a 106.8 lm/W nominal luminous efficacy.

The mounting frame is made of aluminium, with a translucent finish. The ingress protection degree is IP40;

The total absorbed power is 20 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features	
Source lumens	2135 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
LED Life / Failure Ratio	
L80 B20 C0 80000h	