





Ceiling Lights | 220-240 V | topLED 11 W 500 mA | CRI 90
90326



| Technical data | |
|--|-----------------------|
| Type | Surface |
| Installation position | Wall lights - Ceiling |
| Installation environment | Indoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | downward |
| Power | 11 W |
| Source lumens | 1211 lm |
| Frequency | 60 - 50 Hz |
| CCT / Tone | 3000 K |
| Colour rendering index | 90 Ra |
| Safety class | 1 |
| IP | IP40 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Fire Rated (BS 476 PT21 compliant) | No |
| Driver included | Driver |
| Induction | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Double emission |

| Finishing diffuser | |
|--------------------|----------------|
| Material | PMMA |
| Colour | white |
| Processing | Silk-screening |



Ceiling Lights | 220-240 V | topLED 11 W 500 mA | CRI 90
90326

Double emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 24 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1211 lm, with a 110.1 lm/W nominal luminous efficacy.

The diffuser is made of pmma with a silk-screening treatment; the mounting frame is made of aluminium, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40;

The total absorbed power is 11 W.

The device features protection class I and can be wall lights or ceiling-mounted.

Illuminotechnical Features

| | |
|---------------------------------------|----------------|
| Source lumens | 1211 lm |
| Colour temperature | 3000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 90 Ra |

LED Life / Failure Ratio

L80 B20 C0 80000h