

# PRODUCT DATASHEET P CLAS A 75 FR 10.5 W/2700K E27

## PARATHOM CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



## AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

- Very long lifetime of up to 25,000 h
- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

#### **PRODUCT FEATURES**

- LED alternative to conventional lamps
- Good quality of light; color rendering index  $R_a$ :  $\geq$  80; constant chromaticity
- High color consistency: < 6 SDCM</li>
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps



May 25, 2019, 12:24:54 P CLAS A 75 FR 10.5 W/2700K E27

### **TECHNICAL DATA**

#### Electrical data

Rated wattage	10.50 W
Nominal wattage	10.50 W
Nominal voltage	220240 V
Operating frequency	5060 Hz
Power factor $\lambda$	> 0.80
Claimed equiv. conventional lamp power	75 W

### Photometrical data

Nominal luminous flux	1055 lm
Rated luminous flux	1055 lm
Rated color temperature	2700 К
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 К
Luminous flux	1055 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Color rendering index Ra	≥80

## Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

#### Dimensions & weight



Overall length	115.0 mm
Diameter	60.0 mm
Outer bulb	A60

#### PRODUCT DATASHEET

Length	115.0 mm
Lifernan	

#### Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

#### Additional product data

Base (standard designation)	E27		
Mercury content	0.0 mg		
Mercury-free	Yes		
Design / version	Frosted		
Show WEEE picto	Yes		
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/In development, data preliminary/In preparation/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the		

dimmer or the transformer (harmonics or electronic resonance)

## Capabilities

Dimmable	Yes	
Certificates & standards		
Energy efficiency class	A+	
Energy consumption	11 kWh/1000h	

Order reference	LEDPCLA75D 10,5

#### Light Distribution



#### LDC typ polar

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075100992	Folding carton box 1	60 mm x 60 mm x 120 mm	95.00 g	0.43 dm <sup>3</sup>
4058075101005	Shipping carton box 10	315 mm x 131 mm x 126 mm	1063.00 g	5.20 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **REFERENCES / LINKS**

For dimming conformity see

www.ledvance.com/dim

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.