




Wall Lights | 220-240 V | 1xE14  
4405



Technical data	
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Lamp cap	1 x E14 Max 30W
Frequency	50-60 Hz
Optic	Diff. + Diff. + Diff.
Light emission direction	downward
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	Yes
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing diffuser	
Material	Glass
Colour	white
Processing	Sandblasting
Finishing mounting frame	
Material	Iron
Colour	chrome
Processing	Electroplating



Wall Lights | 220-240 V | 1xE14  
**4405**

Single emission wall lights for indoor application. Compatibility: LED lamp, halogen 30 W, compact fluo 8 W; lamp cap 1xE14.

The diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a chrome finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 0.615 kg.

The device features protection class I and can be wall lights or ceiling-mounted.

<b>Illuminotechnical Features</b>	
Luminous flux (source)	835 lm
Colour temperature	2800 K
Colour rendering index	100 Ra