




Wall Lights | 220-240 V | 1xE14  
4425



| Technical data                                 |                       |
|--|-----------------------|
| Installation position                          | Wall lights - Ceiling |
| Installation environment                       | Indoor                |
| Lamp cap                                       | 1 x E14 Max 30W       |
| Frequency                                      | 50-60 Hz              |
| Optic  | Diff. + Diff. + Diff. |
| Light emission direction                       | downward              |
| Safety class                                   | 1                     |
| IP   | IP20                  |
| Glow wire test                                 | 850°                  |
| Direct mounting on normally flammable surfaces | Yes                   |
| CE   | Yes                   |
| ETL  | No                    |
| Induzione                                      | No                    |
| Emergency mode                                 | No                    |
| Motion sensor                                  | No                    |
| Directional                                    | Yes                   |
| Tilting  | No                    |
| Walk-over                                      | No                    |
| Drive-over                                     | No                    |
| Cable included                                 | No                    |
| Resin potting                                  | No                    |

| Finishing diffuser |              |
|--------------------|--------------|
| Material           | Glass        |
| Colour             | white        |
| Processing         | Sandblasting |

| Finishing mounting frame |                |
|--------------------------|----------------|
| Material                 | Iron           |
| Colour                   | nickel         |
| Processing               | Electroplating |



Wall Lights | 220-240 V | 1xE14  
**4425**

Single emission wall lights for indoor application. Compatibility: LED lamp, halogen 30 W, compact fluo 8 W; lamp cap 1xE14.

The diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a nickel finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 0.615 kg.

The device features protection class I and can be wall lights or ceiling-mounted.

| <b>Illuminotechnical Features</b> |        |
|-----------------------------------|--------|
| Luminous flux (source)            | 835 lm |
| Colour temperature                | 2800 K |
| Colour rendering index            | 100 Ra |