



Wall Lights | 220-240 V | 1x2G11  
6725



Technical data	
Installation position	Wall lights
Installation environment	Indoor
Power	1 x 36 W
Lamp cap	1 x 2G11
Frequency	60 - 50 Hz
Optics	General Lighting
Light emission direction	downward and upward
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Induzione	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Net weight	1.665 Kg

Finishing casing	
Material	Iron
Colour	nickel
Processing	Electroplating

Finishing diffuser	
Material	Glass
Colour	white
Processing	Sandblasting

Finishing mounting frame	
Material	Iron
Colour	white
Processing	Coating

Wall Lights | 220-240 V | 1x2G11  
6725

Double emission wall lights for indoor application. Fluorescent lamp included 36W, lamp cap 1x2G11.

The device body is made of iron and features a nickel finish, processed by means of electroplating; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 1.665 kg. The power supply driver is included in the delivery.

The device features protection class I and can be wall lights-mounted.

#### Illuminotechnical Features

Light Output Ratio (LOR)	33 %
Luminous flux (source)	2900 lm
Luminaire luminous flux	973 lm
Consumption	35 W
Luminaire efficacy	82 lm/W
Colour temperature	3000 K
Colour rendering index	80 Ra

