



220-240 V | topLED 28 W 700 mA | CRI 90
8775N



| Technical data | |
|--|------------------|
| Installation position | Wall lights |
| Installation environment | Indoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | upward |
| Power | 28 W |
| Luminous flux (source) | 3730 lm |
| Frequency | 60 - 50 Hz |
| CCT / Tonalità | 4000 K |
| Colour rendering index | 90 Ra |
| Safety class | 1 |
| IP | IP40 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | No |
| CE | No |
| ETL | No |
| Driver included | Yes |
| Dimmable article | Phase cut |
| Induzione | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Net weight | 1 Kg |

| Finishing diffuser | |
|--------------------|---------|
| Material | PMMA |
| Colour | opaline |

| Finishing mounting frame | |
|--------------------------|-----------------|
| Material | Iron |
| Colour | Beton dark grey |
| Processing | Coating |



220-240 V | topLED 28 W 700 mA | CRI 90
8775N

Double emission wall lights for indoor application. The natural white LED light source with a general lighting light distribution is composed of 72 topLED LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 3730 lm, with a 133.2 lm/W nominal luminous efficacy and an operating lifetime (L70) of 72.5000 hours.

The diffuser is made of pmma; the mounting frame is made of iron, with a beton dark grey finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 1 kg. The power supply driver is included in the delivery.


The total absorbed power is 28 W.

The device features protection class I and can be wall lights-mounted.

| Illuminotechnical Features | |
|---------------------------------------|----------------|
| Luminous flux (source) | 3730 lm |
| Colour temperature | 4000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 90 Ra |
| Life / Failure ratio | L70C0B20 72.5H |



Box_W1 | Wall Lights | Accessories
8775N



Dimmer
PUSH DIM, 220-240V

Code
KIT0026